

ARTICLE: JORA-CARE WAX POLISH JCW 940

SYSTEM: WAX POLSIH

PRODUCT PROPERTIES		SCOPE OF APPLICATION
<p>Careline are care and cleaning products. They are not only used for the cleaning of your surface, but also for a lasting preservation of value in all areas.</p> <p>Wax polish for the care of finished parquet.</p> <p>Jora-Care Wax Polish provides effective edge protection. A thin protective film forms on the cut edges. The wax polish is highly productive, one litre is sufficient for at least 200 m².</p>		<p>JORA -CARE Wax Polish is a liquid wax mixture for the care of sealed parquet flooring. It is particularly suitable for initial care directly after parquet laying.</p>
TECHNICAL DATA		APPLICATION
<ul style="list-style-type: none"> ▪ Color: opaque ▪ Dosing: 1 liter/ approx. 200 m² 		<p>Use the wax polish undiluted and do not add to the mopping water!</p> <p>Care: Vacuum the parquet floor and then wipe it lightly with a damp cloth (e.g. with JORA -CLEAN BASIC CLEANER) and let it dry. Apply thinly with a cloth or a single-disc machine and a white pad, rub in and allow to dry for approx. 20 minutes. Then polish the surface with a dry cloth or carpet residue or a white pad.</p> <p>Professional cleaning: Massage in with the single-disc polishing machine and then polish with a white polishing pad. If necessary, rub/absorb excess material with a lint-free cotton cloth.</p>
STORAGE		SPECIAL GUIDANCE
<p>Storage:</p> <p>Store material in a tightly closed container</p> <p>Don't store below 5°C.</p> <p>Shelf-Life:</p> <p>12 months (when stored in the original unopened containers)</p>		<ul style="list-style-type: none"> ▪ Shake well before use! ▪ The usual precautions for handling chemicals must be observed. ▪ Do not allow to enter drains or waters. ▪ Keep out of reach of children. ▪ In the case of parquet which has been sealed on site, initial care must only be applied after approx. 15 days (after complete hardening of the varnish).

Item No.: JCW 940

Safety guidance:

The information in this technical data sheet is based on the current knowledge and experience of PLANTAG Coatings GmbH. The product processor is not exempted from its own testing and testing of the products with regard to the intended use as well as the wealth of possible influences during processing and application. Existing laws and regulations are to be observed by the recipient of our products in their own responsibility. Labeling in accordance with the Ordinance on Hazardous Substances and Transport Law can be found in the safety data sheet. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived from our information. Recommendations deviating from the information in our technical data sheets are only binding for us if they have been confirmed in writing. Our terms and conditions are an integral part of this technical information sheet [Nov-19]

PLANTAG Coatings GmbH
 Plantagenweg 34-38
 32758 Detmold
 GERMANY
 Fon: +49 5231 6002 661
 Fax: +49 5231 6002 9661
 E-Mail: info@jordanlacke.de

JORDAN LACKE – a trademark of PLANTAG Coatings GmbH