

Information on the care of oiled wooden floors using ECO-HARTWACHS-FINISH EHF 570 – The quality can be maintained for a long time with the following care instructions.

Indoor climate:

- Maintaining the value of the surface and the well-being of people requires attention to a healthy indoor climate. Especially in winter, sufficient air humidity should be ensured.
- As wood is a natural product, changes can occur with fluctuations in room temperature and humidity.
- A pleasant indoor climate should be constantly in the range of 18-22° C and a relative humidity between 50-65 %.
- Hygrometers can be used to determine the air humidity. These are available in specialised shops.
- If the room climate is too humid or too dry, wood may swell or shrink. The manufacturer takes no liability for this.
- Permanent exposure to light can cause a change in the wood shade, this is normal with natural wood products and cannot be excluded even with appropriate care.

14 days waiting time:

- Allow freshly sealed parquet surfaces to dry out, do not walk on them beforehand (drying time for ECO-HARTWACHS-FINISH EHF 570: 24 hours). Ventilate rooms sufficiently during the first few days. Only clean dry, do not carry out initial care yet. Initial care should be carried out after 14 days at the earliest.

Initial care of oiled surfaces with JORA-CARE MAINTENANCE OIL JCP 955:

- First remove loose dirt by vacuuming or wiping. To do this, add 5% JORA-CARE MAINTENANCE AGENT JCW 930 to the cleaning water and mix well.
- After a drying time of approx. 1 hour, an evenly matt, caring, and protective film is formed.
- Apply JORA-CARE MAINTENANCE OIL JCP 955 pure and thinly. Then massage into the surface using a pad or cloth. For parquet, application with a single-disc machine and a white pad is recommended. If necessary, rub/absorb the excess material with a lint-free cotton cloth. Spread the maintenance oil until no more traces of the pad, etc. are visible in the wet oil film.
- Allow the surface to dry for 3 to 4 hours.
- The application in the living area should be carried out approx. every 6 months, depending on the wear and tear.
- It is generally recommended to have the initial maintenance carried out by a specialised company. This ensures that untreated joint and edge areas are protected against the penetration of dirt and moisture.

The information in this technical information sheet is based on our current knowledge and experience. Due to the wide range of possible influences during the processing and application of our products, they do not exempt the processor from carrying out his own tests and trials. A legally binding assurance of certain properties or suitability for a specific application cannot be derived from our information. Existing laws and regulations must be observed by the recipient of our products as their own responsibility.

Cleaning with JORA-CARE MAINTENANCE AGENT JCW 930:

- Shake JORA-CARE MAINTENANCE AGENT JCW 930 well before use!
- First remove the loose dirt from the surface.
- Add 1% of JORA-CARE MAINTENANCE AGENT JCW 930 (50 ml to 5 l of water) to the cleaning water and mix well.
- Damp wipe the surface with the care cleaning water.
- Drying time: approx. 1 hour.

Maintenance care with JORA-CARE WAX POLISH JCW 940:

- Vacuum clean the parquet floor, then damp clean (JORA-CARE MAINTENANCE AGENT JCW 930) and allow to dry.
- Shake JORA-CARE WAX POLISH JCW 940 well before use!
- Apply thinly with a cloth and leave to dry for approx. 20 minutes. Then polish the floor with a dry cloth or carpet remnants.
- For matt surfaces, test the product beforehand on hidden areas or on a sample.
- Maintenance care should be applied regularly in case of heavy use.
- For larger surfaces, it is advisable to have the maintenance carried out by a specialist company using a single-disc machine with a white pad.

Notes on value preservation:

Permanent protection of the surface of heavily used areas is achieved by timely sanding and resealing of the floor. The feet or wheels of movable furniture should be fitted with suitable underlays (e.g., felt glides) for optimum protection of the floor. If anti-slip carpet underlays are used, they must not contain any plasticisers, otherwise marks may appear on the floor. Please use latex-based underlays, as these are plasticiser-free. It is recommended to use dirt traps or clean zones to prevent the penetration of coarse dirt. Never use all-purpose cleaners containing ammonia.

- Never expose the surface to moisture or wetness for a long time, as this can lead to swelling. Wipe the surfaces only damp, with wrung-out cloths.
- Do not allow cleaning water to accumulate on the surface.

Precautions:

- Risk of spontaneous combustion with cloth or paper towels wetted with natural oil or furniture oil products (autoxidation)!
- Soaked application wipes and cloths should therefore be dried outdoors or stored in a closed, fireproof container.
- With oil soaked rags can also be kept covered with water for at least 48 hours. After that period, they can then be disposed of. Keep away from oxygen and light.
- The cleaning and care products must be stored under lock and key and out of reach from children, as they may be harmful to health.

The information in this technical information sheet is based on our current knowledge and experience. Due to the wide range of possible influences during the processing and application of our products, they do not exempt the processor from carrying out his own tests and trials. A legally binding assurance of certain properties or suitability for a specific application cannot be derived from our information. Existing laws and regulations must be observed by the recipient of our products as their own responsibility.