

## **Information on the care of lacquered surfaces – The quality of the furniture surfaces can be maintained for a long time with the following care instructions.**

### **Indoor climate:**

- Maintaining the value of the surface and the well-being of people requires attention to a healthy indoor climate. Especially in winter, sufficient air humidity should be ensured.
- As wood is a natural product, changes can occur with fluctuations in room temperature and humidity.
- A pleasant indoor climate should be constantly in the range of 18-22° C and a relative humidity between 50-65 %.
- Hygrometers can be used to determine the air humidity. These are available in specialised shops.
- If the room climate is too humid or too dry, wood may swell or shrink. The manufacturer takes no liability for this.
- Permanent exposure to light can cause a change in the wood shade, this is normal with natural wood products and cannot be excluded even with appropriate care.

### **Instructions for cleaning and care:**

#### **Maintenance cleaning:**

- For regular maintenance cleaning, a soft, lint-free duster and damp wiping is sufficient.
- The first damp cleaning should not be carried out before the coating has been cured for approx. 10 days.
- Lukewarm water without added detergents is suitable for this purpose. A soft, lint-free jersey cloth or a cotton cloth is best suited for this purpose.

#### **Basic cleaning:**

- Aggressive household cleaners or abrasive substances are unsuitable for cleaning the lacquered surfaces.
- In case of heavy soiling, we recommend JORA-CLEAN BASIC CLEANER JCG 920.
- Shake the JORA-CLEAN BASIC CLEANER JCG 920 well before use!
- Spray on JORA-CLEAN BASIC CLEANER JCG 920, spread thinly and evenly and allow it to work for a short time. Then wipe up with an absorbent cloth or sponge.
- Always damp wipe the surface treated with the basic cleaner with water and allow to dry. Afterwards, normal maintenance can be carried out.
- Working with too much water can lead to swelling of the fibres and/or discolouration of the wood.
- Adjacent surfaces must be protected from the penetration of the basic cleaner.

The information in this technical information sheet is based on our current knowledge and experience. Due to the wide range of possible influences during the processing and application of our products, they do not exempt the processor from carrying out his own tests and trials. A legally binding assurance of certain properties or suitability for a specific application cannot be derived from our information. Existing laws and regulations must be observed by the recipient of our products as their own responsibility.

## Care:

- Remove loose dirt from the surface. In case of heavy soiling, wipe first with JORA-CLEAN BASIC CLEANER JCG 920 (see basic cleaning).
- Add 1% of JORA-CARE MAINTENANCE AGENT JCW 930 (50 ml to 5 l of water) to the cleaning water and mix well.
- Using a cleaning cloth or a chamois wet in the cleaning water, wring out and wipe the surface lightly.
- The maintenance agent is to be used depending on the intensity of the stress and wear. Do not soak the surface.
- After a drying time of approx. 1 hour, an evenly spread, caring and matt protective film is created.

## Notes on value preservation:

- Never expose the surface to moisture or wetness for a long period, as this can lead to swelling. Wipe the surfaces using only damp, wrung-out cloths.
- Do not allow cleaning water to accumulate on the surface.
- Do not use abrasive microfibre cloths as the coating can be harmed.
- Use plasticiser-free coasters to avoid spots on the surface caused by plasticisers.

## Precautions:

- The cleaning and care products must be stored under lock and key and out of reach from children, as they may be harmful to health.

The information in this technical information sheet is based on our current knowledge and experience. Due to the wide range of possible influences during the processing and application of our products, they do not exempt the processor from carrying out his own tests and trials. A legally binding assurance of certain properties or suitability for a specific application cannot be derived from our information. Existing laws and regulations must be observed by the recipient of our products as their own responsibility.